

Designation 型号	Principal dimensions 基本尺寸			Basic load ratings (KN) 基本额定负荷		Pu 疲劳寿命 系数	Speed ratings 额定转速		Weight 重量	Dimensions (mm) 尺寸										Abutment and fillet dimensions (mm) 安装尺寸			Value 计算系数		
	d <sub>i</sub>	D	B	dyc	stc		Speed Ratings (rpm)	Limiting Speed		d	d <sub>i</sub> ~	D1	B	C	C1	r <sub>1,2</sub>	r <sub>3,4</sub>	a	d <sub>a</sub>	d <sub>b</sub>	r <sub>a</sub>	e	Y	Y <sub>0</sub>	
																Min	Min								Max
	(mm)			Cr	Cor												Max	Min	Max						
3200RXR/QVA621	40	68	19	60	71	7.65	7500	9500	0.27	40	54.2	72	19	14.5	3.5	1	1	15	46	46	1	0.37	1.6	0.9	
3020RLZ/Q	40	80	19.75	71	68	7.65	7000	8500	0.42	40	57.5	85	18	16	4	1.5	1.5	16	49	47	1	0.37	1.6	0.9	
3230BRQ	45	85	32	105	143	16.3	5300	7500	0.65	45	65.2	90	32	25	5	1.5	1.5	22	52	52	1	0.4	1.5	0.8	
3230BRZ/QCL7C	45	100	38.25	156	176	20	5000	6700	1.50	45	74.8	106	36	30	7	2	1.5	30	55	54	1.5	0.54	1.1	0.6	
32311BRZ/QCL7C	55	120	45.5	216	260	30	4300	5600	2.50	55	90.5	127	43	35	8	2.5	2	36	67	65	2	0.54	1.1	0.6	
30313RQ	65	110	34	142	205	24	4300	5600	1.30	65	87.9	116	34	26.5	5.5	1.5	1.5	26	74	72	1	0.4	1.5	0.8	
30313RL2	65	140	36	194	225	27.5	3600	4800	2.40	65	96.3	147	33	28	6	3	2.5	28	84	77	2	0.35	1.7	0.9	
30313RL2	65	140	36	194	225	27.5	3600	4800	2.40	65	96.3	147	33	28	6	3	2.5	28	84	77	2	0.35	1.7	0.9	