

Bearing No.	Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (rpm)		Weight
	尺寸				额定负荷极限		极限转速		重量
轴承型号	d	D	B	r _{s min}	Dynamic (Cr)	Static (Cor)	Grease	Oil	
					动载	静载	脂	油	Kg
22308	40	90	33	1.5	121	128	3,800	5,900	0.974
22308K	40	90	33	1.5	121	128	3,800	5,900	0.951
22308KW33C3	40	90	33	1.5	121	128	3,800	5,900	0.951
22308W33C3	40	90	33	1.5	121	128	3,800	5,900	0.974
22309	45	100	36	1.5	148	167	3,400	5,300	1.33
22309K	45	100	36	1.5	148	167	3,400	5,300	1.3
22309KW33C3	45	100	36	1.5	148	167	3,400	5,300	1.3
22309W33C3	45	100	36	1.5	148	167	3,400	5,300	1.33
22310	50	110	40	2	186	212	3,100	4,800	1.79
22310K	50	110	40	2	186	212	3,100	4,800	1.75
22310KW33C3	50	110	40	2	186	212	3,100	4,800	1.75
22310W33C3	50	110	40	2	186	212	3,100	4,800	1.79
22311	55	120	43	2	204	234	2,800	4,400	2.3
22311K	55	120	43	2	204	234	2,800	4,400	2.25
22311KW33C3	55	120	43	2	204	234	2,800	4,400	2.25
22311W33C3	55	120	43	2	204	234	2,800	4,400	2.3
22312	60	130	46	2.1	238	273	2,600	4,000	2.9
22312K	60	130	46	2.1	238	273	2,600	4,000	2.83
22312KW33C3	60	130	46	2.1	238	273	2,600	4,000	2.83
22312W33C3	60	130	46	2.1	238	273	2,600	4,000	2.9
22313	65	140	48	2.1	265	320	2,400	3,700	3.45
22313K	65	140	48	2.1	265	320	2,400	3,700	3.37
22313KW33C3	65	140	48	2.1	265	320	2,400	3,700	3.37
22313W33C3	65	140	48	2.1	265	320	2,400	3,700	3.45
22314	70	150	51	2.1	325	380	2,300	3,500	4.22
22314K	70	150	51	2.1	325	380	2,300	3,500	4.12
22314KW33C3	70	150	51	2.1	325	380	2,300	3,500	4.12
22314W33C3	70	150	51	2.1	325	380	2,300	3,500	4.22
22315	75	160	55	2.1	330	410	2,100	3,200	5.25
22315K	75	160	55	2.1	330	410	2,100	3,200	5.13
22315KW33C3	75	160	55	2.1	330	410	2,100	3,200	5.13
22315W33C3	75	160	55	2.1	330	410	2,100	3,200	5.25

22316	80	170	58	2.1	385	470	2,000	3,000	6.05
22316K	80	170	58	2.1	385	470	2,000	3,000	5.91
22316KW33C3	80	170	58	2.1	385	470	2,000	3,000	5.91
22316W33C3	80	170	58	2.1	385	470	2,000	3,000	6.05
22317	85	180	60	3	415	510	1,900	2,900	7.1
22317K	85	180	60	3	415	510	1,900	2,900	6.94
22317KW33C3	85	180	60	3	415	510	1,900	2,900	6.94
22317W33C3	85	180	60	3	415	510	1,900	2,900	7.1
22318	90	190	64	3	480	590	1,800	2,700	8.35
22318K	90	190	64	3	480	590	1,800	2,700	8.16
22318KW33C3	90	190	64	3	480	590	1,800	2,700	8.16
22318W33C3	90	190	64	3	480	590	1,800	2,700	8.35
22319	95	200	67	3	500	615	1,600	2,500	9.76
22319K	95	200	67	3	500	615	1,600	2,500	9.54
22319KW33C3	95	200	67	3	500	615	1,600	2,500	9.54
22319W33C3	95	200	67	3	500	615	1,600	2,500	9.76
22320	100	215	73	3	605	755	1,600	2,400	12.4
22320K	100	215	73	3	605	755	1,600	2,400	12.1
22320KW33C3	100	215	73	3	605	755	1,600	2,400	12.1
22320W33C3	100	215	73	3	605	755	1,600	2,400	12.4
22322	110	240	80	3	745	930	1,400	2,200	17.1
22322K	110	240	80	3	745	930	1,400	2,200	16.7
22322KW33C3	110	240	80	3	745	930	1,400	2,200	16.7
22322W33C3	110	240	80	3	745	930	1,400	2,200	17.1
22324	120	260	86	3	880	1,120	1,300	2,000	21.5
22324K	120	260	86	3	880	1,120	1,300	2,000	21
22324KW33C3	120	260	86	3	880	1,120	1,300	2,000	21
22324W33C3	120	260	86	3	880	1,120	1,300	2,000	21.5
22326	130	280	93	4	1,000	1,290	1,200	1,800	26.8
22326K	130	280	93	4	1,000	1,290	1,200	1,800	26.2
22326KW33C3	130	280	93	4	1,000	1,290	1,200	1,800	26.2
22326W33C3	130	280	93	4	1,000	1,290	1,200	1,800	26.8
22328	140	300	102	4	1,130	1,460	1,100	1,700	33.8
22328K	140	300	102	4	1,130	1,460	1,100	1,700	33
22328KW33C3	140	300	102	4	1,130	1,460	1,100	1,700	33
22328W33C3	140	300	102	4	1,130	1,460	1,100	1,700	33.8
22330	150	320	108	4	1,270	1,750	1,000	1,600	42.7
22330K	150	320	108	4	1,270	1,750	1,000	1,600	41.8
22330KW33C3	150	320	108	4	1,270	1,750	1,000	1,600	41.8

22330W33C3	150	320	108	4	1,270	1,750	1,000	1,600	42.7
22332	160	340	114	4	1,410	1,990	940	1,500	50.8
22332K	160	340	114	4	1,410	1,990	940	1,500	49.7
22332KW33C3	160	340	114	4	1,410	1,990	940	1,500	49.7
22332W33C3	160	340	114	4	1,410	1,990	940	1,500	50.8
22334	170	360	120	4	1,540	2,180	880	1,400	59.8
22334K	170	360	120	4	1,540	2,180	880	1,400	58.5
22334KW33C3	170	360	120	4	1,540	2,180	880	1,400	58.5
22334W33C3	170	360	120	4	1,540	2,180	880	1,400	59.8
22336	180	380	126	4	1,740	2,560	830	1,300	70
22336K	180	380	126	4	1,740	2,560	830	1,300	68.5
22336KW33C3	180	380	126	4	1,740	2,560	830	1,300	68.5
22336W33C3	180	380	126	4	1,740	2,560	830	1,300	70
22338	190	400	132	5	1,870	2,790	780	1,200	81
22338K	190	400	132	5	1,870	2,790	780	1,200	79.3
22338KW33C3	190	400	132	5	1,870	2,790	780	1,200	79.3
22338W33C3	190	400	132	5	1,870	2,790	780	1,200	81
22340	200	420	138	5	2,040	3,050	740	1,100	93.2
22340K	200	420	138	5	2,040	3,050	740	1,100	91.2
22340KW33C3	200	420	138	5	2,040	3,050	740	1,100	91.2
22340W33C3	200	420	138	5	2,040	3,050	740	1,100	93.2
22344	220	460	145	5	2,350	3,500	660	1,000	117
22344K	220	460	145	5	2,350	3,500	660	1,000	115
22344KW33C3	220	460	145	5	2,350	3,500	660	1,000	115
22344W33C3	220	460	145	5	2,350	3,500	660	1,000	117
22348	240	500	155	5	2,720	4,100	600	930	148
22348K	240	500	155	5	2,720	4,100	600	930	145
22348KW33C3	240	500	155	5	2,720	4,100	600	930	145
22348W33C3	240	500	155	5	2,720	4,100	600	930	148
22352	260	540	165	6	3,100	4,750	550	850	183
22352K	260	540	165	6	3,100	4,750	550	850	179
22352KW33C3	260	540	165	6	3,100	4,750	550	850	179
22352W33C3	260	540	165	6	3,100	4,750	550	850	183
22356	280	580	175	6	3,500	5,350	500	780	224
22356K	280	580	175	6	3,500	5,350	500	780	220
22356KW33C3	280	580	175	6	3,500	5,350	500	780	220
22356W33C3	280	580	175	6	3,500	5,350	500	780	224
22360	300	620	185	7.5	3,600	5,400	470	720	270
22360K	300	620	185	7.5	3,600	5,400	470	720	265

22360KW33C3	300	620	185	7.5	3,600	5,400	470	720	265
22360W33C3	300	620	185	7.5	3,600	5,400	470	720	270