

Bearing No.	Boundary dimensions (mm)					Basic load rating(kN)		Limiting speeds (rpm)		Weight(Kg)
	基本尺寸					额定负荷		极限转速		
型号	d	D	B	$r_{s\ min}$	$r_{s1\ min}$	Dynamic (Cr)	Static (Cor)	Grease	Oil	重量
				$r_{s\ 最小}$	$r_{s1\ 最小}$	动载	静载	脂	油	
N208	40	80	18	1.1	1.1	43.5	43	9,400	11,000	0.37
N209	45	85	19	1.1	1.1	46	47	8,400	9,900	0.423
N210	50	90	20	1.1	1.1	48	51	7,600	9,000	0.46
N211	55	100	21	1.5	1.1	58	62.5	6,900	8,200	0.626
N212	60	110	22	1.5	1.5	68.5	75	6,400	7,600	0.802
N213	65	120	23	1.5	1.5	84	94.5	5,900	7,000	1
N214	70	125	24	1.5	1.5	83.5	95	5,500	6,500	1.1
N215	75	130	25	1.5	1.5	96.5	111	5,100	6,000	1.21
N216	80	140	26	2	2	106	122	4,800	5,700	1.47
N217	85	150	28	2	2	120	140	4,500	5,300	1.83
N218	90	160	30	2	2	152	178	4,300	5,000	2.25
N219	95	170	32	2.1	2.1	166	195	4,000	4,700	2.72
N220	100	180	34	2.1	2.1	183	217	3,800	4,500	3.26
N221	105	190	36	2.1	2.1	201	241	3,600	4,300	3.87
N222	110	200	38	2.1	2.1	240	290	3,400	4,000	4.54
N224	120	215	40	2.1	2.1	260	320	3,200	3,700	5.46
N226	130	230	40	3	3	270	340	2,900	3,400	6.17
N228	140	250	42	3	3	310	400	2,700	3,100	7.72
N230	150	270	45	3	3	345	435	2,500	2,900	9.72