

Designation				Dimensions	Dimensions						Weight
				in	mm						
With Lock nut	Lock nut	Locking Set	Appropriate hydraulic nuts	d ₁	d ₁	d	d ₃	B ₁	B ₂	G	
Locking Adapter Sleeve				d ₁	d	d ₃	B ₁	B ₂	G		
HA3024	KML24	MBL24	HMV24E	4 3/16	106,363	120	145	72	22	M120×2	2,25
HA3024E	KMFE24	-	HMV24E	4 3/16	106,363	120	155	72	26	M120×2	2,32
HA3026	KML26	MBL26	HMV26E	4 7/16	112,713	130	155	80	23	M130×2	3,05
HA3028	KML28	MBL28	HMV28E	4 15/16	125,413	140	165	82	24	M140×2	3,00
HA3030	KML30	MBL30	HMV30E	5 3/16	131,763	150	180	87	26	M150×2	4,20
HA3032	KML32	MBL32	HMV32E	5 7/16	138,113	160	190	93	27,5	M160×3	5,40
HA3034	KML34	MBL34	HMV34E	5 15/16	150,813	170	200	101	28,5	M170×3	5,70
HA3036	KML36	MBL36	HMV36E	6 7/16	163,513	180	210	109	29,5	M180×3	6,00
HA3038	KML38	MBL38	HMV38E	6 15/16	176,213	190	220	112	30,5	M190×3	5,80
HA3040	KML40	MBL40	HMV40E	7 3/16	182,563	200	240	120	31,5	M200×3	8,25
HE3024E	KMFE24	-	HMV24E	4 1/4	107,950	120	155	72	26	M120×2	2,70
HE3026	KML26	MBL26	HMV26E	4 1/2	114,300	130	155	80	23	M130×2	2,90
HE3028	KML28	MBL28	HMV28E	5	127,000	140	165	82	24	M140×2	2,80
HE3030	KML30	MBL30	HMV30E	5 1/4	133,350	150	180	87	26	M150×2	4,00
HE3032	KML32	MBL32	HMV32E	5 1/2	139,700	160	190	93	27,5	M160×3	5,10
HE3034	KML34	MBL34	HMV34E	6	152,400	170	200	101	28,5	M170×3	5,40
HE3036	KML36	MBL36	HMV36E	6 1/2	165,100	180	210	109	29,5	M180×3	5,55
HE3038	KML38	MBL38	HMV38E	6 3/4	171,450	190	220	112	30,5	M190×3	7,20
HE3040	KML40	MBL40	HMV40E	7	177,800	200	240	120	31,5	M200×3	9,35