


3-bolt bracket flanged ball bearing units, set screws, for metric shafts d 30-45mm



Principal dimensions	Basic load ratings (KN)		Fatigue load (Pu)	Limiting speed with shaft tolerance h6	Mass (Kg)	Designation			Unit	Dimensions (mm)														
	d	dynamic static(C)				limit C0	Housing	Bearing		Appropriate end cover	d	H	L	A	J	J1	N	H1	L1	A1	A5	T	B	S1
30	19,5	11,4	0,5	5000	0,98	FB 206	UC206	ECY206	UCFB 206	30	136,5	82,6	30	40	29	9,5	50	69,9	9,5	22,5	40,9	38,1	15,9	M8
35	25,5	15,3	0,7	4300	1,29	FB 207	UC207	ECY207	UCFB 207	35	144	90	33,5	46	32	9,5	55	82,6	12,7	24,5	44,4	42,9	17,5	M8
40	32,5	20,0	0,9	3750	1,70	FB 208	UC208	ECY208	UCFB 208	40	164,3	100	35,7	50	41	11	60	77,8	15,9	26	51,2	49,2	19	M10
45	32,5	20,4	0,9	3400	1,99	FB 209	UC209	ECY209	UCFB 209	45	175,5	106,4	36,8	54	43	11	65	80,2	18,3	26,5	50,2	49,2	19	M10